



• Features

SMD LED Chip imported from Taiwan, low power consumption, high efficiency, long service time.
 High quality die cast aluminium, corrosion resistant, anti-cracking.
 Housing coat color optional : White/Black/Dark Bronze/Silver Grey
 UL listed for wet locations, Ip65
 LM79, IES test reports available
 Certification: UL, cUL, DLC, FCC, SAA, CE, RoHS, CB, C-TICK
 Suitable for use in -40 °C to 50 °C

• Application

Widely used in building facades, plaza, garden landscape, golf courses, villas, parks, farms and other outdoor places.

• Technical Data

Specification	SFL1-20	SFL1-30	SFL1-50	SFL1-75
Power	20W	30W	50W	75W
Luminous Flux	1600lm	2400lm	4000lm	6000lm
Efficacy	80lm/W	80lm/W	80lm/W	80lm/W
Color Temperature	3000K/4000K/5000K/5700K			
Input Voltage	AC100-277V 50-60HZ			
Power Factor	> 0.95			
Life Time(hrs)	50000			
CRI	72			
Finish color	White/Black/Dark Bronze/Silver Grey			
Dimension(L x W x H)mm	180 x 140 x 110	180 x 140 x 110	225 x 185 x 125	285 x 235 x 140

Specification	SFL1-100	SFL1-150	SFL1-200	LFL1-200
Power	100W	150W	200W	200W
Luminous Flux	8000lm	12000lm	16000lm	16000lm
Efficacy	80lm/W	80lm/W	80lm/W	80lm/W
Color Temperature	3000K/4000K/5000K/5700K			
Input Voltage	AC100-277V 50-60HZ			
Power Factor	> 0.95			
Life Time(hrs)	50000			
CRI	72			
Finish color	White/Black/Dark Bronze/Silver Grey			
Dimension(L x W x H)mm	285 x 235 x 140	285 x 365 x 100	452 x 320 x 160	452 x 320 x 180

