



• Features

- Ultra slim design, fashion and Luxury
- High quality die cast aluminium, corrosion resistant, anti-cracking.
- Housing coat color optional : Black/White/Dark Bronze
- Installation Arm is optional
- UL Listed for wet locations, IP65
- Suitable for use in -40°C to 50 °C
- LM79, IES test reports available

• Application

Widely used in building facades, plaza, garden landscape, golf courses, villas, parks, farms and other outdoor places.

• Technical Data

Specification	CSFL-10	CSFL-20	CSFL-30	CSFL-50
Power	10W	20W	30W	50W
Luminous Flux	800lm	1600lm	2400lm	4000lm
Efficacy	80lm/w	80lm/w	80lm/w	80lm/w
Color Temperature	3000K/4000K/5000K/5700K			
Input Voltage	AC 100-277V 50-60Hz			
CRI	72			
Power Factor	> 0.95			
Life Time(hrs)	50000			
Finish Color	Black/White/Dark Bronze			
Dimension(L x W x H)mm	140 x 95 x 28	195 x 135 x 35	241 x 168 x 42	241 x 168 x 42

Specification	CSFL-10A	CSFL-20A	CSFL-30A	CSFL-50A
Power	10W	20W	30W	50W
Luminous Flux	800lm	1600lm	2400lm	4000lm
Efficacy	80lm/w	80lm/w	80lm/w	80lm/w
Arms	Y	Y	Y	Y
Color Temperature	3000K/4000K/5000K/5700K			
Input Voltage	AC 100-277V 50-60Hz			
CRI	72			
Power Factor	> 0.95			
Life Time(hrs)	50000			
Finish Color	Black/White/Dark Bronze			
Dimension(L x W x H)mm	136 x 176 x 28	191 x 216 x 35	237 x 256 x 42	237 x 256 x 42

